

11 Dan Jacobs Street, Alrode, Alberton 1449 P.O. Box 136166, Alberton North 1456

T +27 (11) 389 4600 F +27 (11) 864 2407 (Finance) F +27 (11) 389 4654 (Commercial) W www.prominentpaints.co.za

Material Safety Data Sheet SCUMBLEGLAZE

COMPANY DETAILS

Company Name: PPG Industries – Prominent Paints (Pty) Ltd

Address: 11 Dan Jacobs Ave, Alrode, Alberton, Gauteng

Tel: 011 389 4600 / 0861 776 646

Fax: 011 389 4783

Emergency telephone no.: Spill Emergency: 0800 Health Emergency: 0800 E-mail address: info@ DG ADVISOR: 082 3779 430

0800 17 07 43 (Rapid Spill Response) 0800 33 3444 (Poison Control Centre) info@prominentpaints.co.za 79 430

MSDS prepared by: Johan Batist and Shaleen Olivier

1.

PRODUCT AND COMPANY IDENTIFICATION:

Trade name: SCAMBLEGLAZE

Product use: PAINTING

Common Name: SCAMBLEGLAZE

Chemical family: WATER BASED ACRYLIC PAINT

Synonyms: N/A

UN no.: N/A

Hazard Class: N/A

Chemical name: N/A

CAS No. : N/A

Proper shipping name: N/A

Packing Group: N/A

2. **PRODUCT COMPOSITION:**

EEC classification: Water based, non-hazardous paint related mixture

Hazardous components: None

Components	CAS #	Concentration	Risk Phrase
Acrylic Emulsion	N/A	20-50%	N/A
Pigments	N/A	5-6%	R20/21
Water	7732-18-5	10-30 %	
Ingredients determined not to be hazardous		to 100%	

MSDS No.:	SGZ002	Rev: 02
Date:	27 JUNE 2013	Page 1 of 7

Reg. No. 1997/006763/07





PPG Industries Bringing innovation to the surface.[™]

3. HAZARDS IDENTIFICATION:

Main hazard: A mixture constituting non-hazardous chemical substances.

Irritation or minor reversible injury possible Inhalation: None Skin: May cause slight irritation. Eyes: Over–exposure may cause slight physical irritation. Ingestion: None Known No carcinogenic, mutagenic or genetic effects established

Potential Acute Health Effects: None known

4. FIRST-AID MEASURES

Product in eye: Check for and remove any contact lenses. Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician, if eye irritation persists.

Product on skin: Wash off with soap and plenty of water as a precaution, while removing all contaminated clothes and shoes. If symptoms persist or in all cases of doubt, seek medical advice.

Product ingested: If swallowed, drink 1 to 2 glasses of water. Call a physician if necessary. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

Product inhaled: Remove to fresh air. If in doubt or if symptoms persist, seek medical advice.

Notes to the Physician and special treatment: Treat symptomatically. Contact poison control centre.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing media: Not combustible (water based), however if material is involved in a fire use : extinguishing media appropriate for the surrounding materials. Use water with care to avoid possible violent production of steam.

Protective Clothing: Be sure to use an appropriate/certified respirator or equivalent

In event of a fire avoid breathing vapours. Keep upwind. Fight fire from maximum distance. Beware of toxic fumes. Dyke fire water for later disposal. Remove containers from fire at first safe opportunity.

Hazards from combustion products: Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning, thermal decomposition could yield acrylic monomers.

MSDS No.:	SGZ002	Rev: 02
Date:	27 JUNE 2013	Page 2 of 7





Personal precautions: only use approved and appropriate protective clothing before handling any spilled materials. Safety glasses, goggles or face shield, impervious gloves. Material can cause slippery conditions.

Environmental precautions: Contain and collect. Use an Inert material (not saw dust). Keep waste separate for disposal. Do not allow material to contaminate ground water system.

Evacuate personnel to safe areas. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13). Do not flush into surface water or sanitary sewer system. Wash spillage area with water. Spillage or uncontrolled discharge into watercourses must be reported to the appropriate regulatory body.

Small spills: Slippery when wet. Dilute with water and mop up, or absorb with an inert material, collect spilled material and transfer into a suitable marked container. Wash the spilled area with water.

Large spills: Slippery when wet. Prevent spilled product from entering drains, sewers and water courses. Attempt to contain spill in the area of leak. Remove none compatible materials. Large spillages should be dammed-off and pumped into containers; soak up remainder and dispose of in accordance with local regulations. Do not wash into sewer. Do not flush spilled material into sewer or drains. Keep spectators away. Notify the appropriate Government department.

7. HANDLING AND STORAGE

Handling/storage precautions: Store at temperatures not exceeding 40°C and out of direct sunlight. Avoid contact with skin, eyes and clothing. Store in sealed original containers, well-aired, fresh and dry storage rooms and warehouse or in shaded and possibly well ventilated.

Keep away from direct sunlight, food, seed, animals, children and uninformed persons.

Store in a segregated and approved area and keep containers tightly closed and sealed until ready for use.

Keep out of reach of children.

MSDS No.:	SGZ002	Rev: 02
Date:	27 JUNE 2013	Page 3 of 7
		_

PPG Industries

Bringing innovation to the surface.[™]





Occupational exposure limits: PPE: Eye protection and Gloves

Inhalation: NOTES (SECTION 3)

Skin: Use barrier cream and impervious gloves.

Eyes: Use goggles. Avoid direct contact.

Ingestion: Observe the rules for hygiene. Wash hands before eating, drinking or smoking.

OEL Type: Mix-Mixture-See SECTION 2

Engineering control measures: For occupational exposures, ensure adequate ventilation and use outdoors in a well-ventilated area. The mixing and loading of mixtures into equipment must be carried out on an impervious pad (i.e. concrete slab, plastic sheeting) large enough to catch any spilled material.

If spills occur, contain the spill by using an absorbent material (e.g. sand, earth or synthetic absorbent). Dispose of the contaminated absorbent material by placing in a plastic bag and following disposal instructions on this MSDS.

PEL= Permissible Exposure Limits TLV= Threshold Limit Value EL= Excursion Limit TWA= Time Weighted Average (8 hr.) STEL= Short Term Exposure Limit (15 min.) WEEL= Workplace Environmental Exposure Level

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Auto flammability:	Non-flammable
Colour and Appearance:	Coloured	Explosive properties:	N/A
Odour:	Characteristic odour	Oxidizing properties:	Not Determined
pH:	7.5-9.0	Vapour pressure:	Not determined
Boiling point:	Approx. 100°C	Density:	1.0-1.5
Melting point:	N/A	Solubility - water:	Soluble
Flash point:	N/A	Solubility - solvent:	Miscible
Flammability:	Non Flammable	Solubility coefficient	Not Determined

MSDS No.:	SGZ002	Rev: 02
Date:	27 JUNE 2013	Page 4 of 7



PPG Industries Bringing innovation to the surface.[™]





10. STABILITY AND REACTIVITY

Stability and reactivity: This product is stable under the recommended storage conditions and normal conditions of use.

Conditions to avoid: Avoid contact with foodstuffs.

Hazardous decomposition products: Combustion products include steam and oxides of carbon and possibly other unidentified organic compounds.

Hazardous reactions: None known.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: No adverse effects expected, however, large amounts may cause nausea and vomiting.

Eye contact: May be an eye irritant.

Skin contact: Contact with skin may result in irritation.

Inhalation: Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes of the respiratory tract, headache and nausea.

No carcinogenic, mutagenic or genetic effects established.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways. May cause undesirable effects to aquatic organ

13. DISPOSAL CONSIDERATIONS

Disposal methods: Try to prevent the material from entering drains or water sources do not discharge effluent containing this product to sewer systems.

Dispose of only in accordance with local, national and international regulations, guidelines and treaties. Dispose of in approved landfill. Do not contaminate any lakes, streams, ponds, groundwater or soil.

Do not contaminate crops, grazing, rivers, oceans or dams with chemical or used container. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public water.

Disposal of packaging: Rinse empty container thoroughly, securely wrap empty container in several layers of newspaper or flatten the container and discard in trash or recycle.

Dispose of in approved landfill or preferably in an incinerator. Do not re-use empty containers. Wear appropriate personal protective equipment when cleaning or handling waste material.

MSDS No.:	SGZ002	Rev: 02
Date:	27 JUNE 2013	Page 5 of 7





14. TRANSPORT INFORMATION

UN no.:	N/A
ADR/RID class:	Not regulated (Not dangerous for transport)
Packing Group:	N/A
ADR/RID item no.:	N/A
ADR/RID hazard identity no.:	N/A
IMDG - shipping name:	Not regulated (Not dangerous for transport)
IMDG - class:	N/A
IMDG - packaging group:	N/A
IMDG - marine pollutant:	Not regulated (Not dangerous for transport)
IMDG - EMS no.:	Not available
IMDG - WAG tabel no.:	N/A
IATA - shipping name:	Waterbased, non-hazardous paint related mixture
IATA - class:	N/A
IATA - subsidiary risk(s):	N/A

15. REGULATORY INFORMATION.

EEC hazard classification: Non-hazardous

Contains mixture of non-hazardous classified: Acrylic emulsion and pigments

Safety phases:	 S2: Keep out of the reach of children S7: Keep container tightly closed S24: Avoid contact with skin S35: This material and its container must be disposed of in a safe way
National legislation: Africa)	Occupational Health and Safety Act no 85 of 1993 (Republic of South
	Hazardous Chemical Substance Act:
	National Road Traffic Act no 93 of 1996 Party to the Basel Convention 05.05.1994 (a)

MSDS No.:	SGZ002	Rev: 02
Date:	27 JUNE 2013	Page 6 of 7



pPG



16. OTHER INFORMATION

NB. Read and understand all the information on the product label before using the product.

This product should only be used as directed on the label and for the purpose intended.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

All information and instructions provided in the Material Safety Data Sheet (MSDS) are based on the current state of scientific and technical data and knowledge at the date indicated on the present MSDS and are presented in good faith and believed to be correct. It is the responsibility of persons in receipt of this MSDS to ensure that the information herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product

MSDS No.:	SGZ002	Rev: 02
Date:	27 JUNE 2013	Page 7 of 7



PPG