

## PROMINENT PAINTS ACRYLIC SEALER

### PRODUCT DESCRIPTION:

A high quality acrylic emulsion.

### INTENDED USES:

1. As a sealer key coat to improve adhesion of unabsorbent surfaces, e.g. previously painted surfaces.
2. As an additive to improve water resistance, adhesion and impact resistance.

### FEATURES:

1. Waterproofs cement plasters.
2. Increases impact resistance of cement plasters.
3. Improves adhesion of cement plasters.
4. Water based – easy application and clean up.

### PRODUCT INFORMATION:

<u>Appearance:</u>	Clear film.
<u>Colours:</u>	Clear.
<u>Solids:</u>	25% by mass.
<u>Density:</u>	1,02Kg/litre.
<u>Recommended Dry Film Thickness:</u>	Not applicable.
<u>Spreading rate:</u>	Not applicable.
<u>Viscosity at 23°C :</u>	± 60Kμ.
<u>Flash point:</u>	Non-flammable.
<u>Respecting the environment:</u>	<b>100% Lead Free.</b> Dispose of excess product and containers in a responsible manner without harming the environment.

**This product is manufactured under strict SABS ISO 9001 quality standards.**

### STORAGE:

Keep containers properly sealed.  
Store away from direct heat, sun and severe cold in a place with adequate ventilation.

### PACKAGING:

1Lt, 5Lt, 20Lt

**PROMINENT PAINTS ACRYLIC SEALER****USAGE DETAILS:**

1. **Mixing:** Stir well before use with a flat paddle to an even consistency. Stir occasionally during use.
2. **Method:** Roller or brush when used as plaster key.
3. **Thinning:** Water.
4. **Cleaning:** Water.
5. **Conditions:** Temperature between 5°C and 40°C. Relative humidity of less than 85%, preferably between 10:00 and 16:00.

**LIMITATIONS:**

1. May not be used as a varnish or topcoat.
2. Not for exterior use.
3. Not for areas prone to traffic e.g. floors.

**SAFETY PRECAUTIONS:**

1. Keep out of reach of children.
2. Ensure to maintain good ventilation during application and drying process.
3. In case of skin contact, wash with soap and water or a recognised skin cleaner. Avoid contact with eyes. In case of contact with eyes rinse immediately with running water and seek medical advice.
4. If product is ingested drink plenty of water or milk. Do not induce vomiting at any time. Seek medical advice.
5. Refer to the Material Safety Data Sheet (MSDS) for detailed information about the product and transportation and classification criteria. MSDS is available on [www.prominentpaints.co.za](http://www.prominentpaints.co.za) or from Prominent Paints Customer Service Department.
6. To avoid any risk of spillage, always transport in a secure upright position.

**DISCLAIMER:**

The information contained herein is given in good faith and is meant merely as a guide for the specifier or user. It is gained from results obtained from our experience and tests carried out under controlled conditions. No warranty/guarantee is implied since the conditions of use, application method, substrate and cleanliness of the substrate are beyond Prominent Paints control. For a surface specific specification contact Prominent Paints Customer Service Department for assistance. This issue supersedes all previous publications.

**Important Note;** Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used for reference. Prominent Paints Technical Data Sheets are available on [www.prominentpaints.co.za](http://www.prominentpaints.co.za) or from Prominent Paints Customer Service Department.

**Prominent Paints (Pty) Ltd.**  
11 Dan Jacobs Street.  
Alrode Alberton 1449  
P.O. Box 136166  
Alberton North 1456

Reg. No. 1997/006763/07

Customer Service Department:  
Tel: +27 86 177 6646  
Fax: +27 11 389 4711  
[www.prominentpaints.co.za](http://www.prominentpaints.co.za)