

PROMINENT PAINTS RIPPLE TROWEL-ON

PRODUCT DESCRIPTION:

Elastomeric acrylic bound specialist protective and decorative finish as an interior/exterior coating with a durable scratch plaster-like textured finish.

INTENDED USES:

1. Interior and exterior walls for hiding plaster defects, minor cracks on correctly prepared and primed Concrete, Plaster, Dry-Walls, Rhino Boards, Fibre Cement, Chip Board, Supawood, Facia-Boards, Masonite and similar material.
2. Interior and exterior walls as a decorative finish.
3. Ideal for buildings where extensive scaffolding is required thus requiring coating with a long life.

FEATURES:

- | | |
|-------------------------|---|
| 1. Durable | Long life external coating. |
| 2. UV Resistant | Inorganic colour-fast pigments. |
| 3. Weather Resistant | Allows the wall to breathe and handle extreme temperature fluctuations. |
| 4. Water based | |
| 5. Minor plaster cracks | Hides plaster cracks which may develop underneath the applied coating. |

PRODUCT INFORMATION:

<u>Appearance:</u>	Scratch plaster-like textured.
<u>Colours:</u>	Soft Ivory.
<u>Solids:</u>	62% by mass.
<u>Density:</u>	1,67kg/litre.
<u>Recommended Dry Film Thickness:</u>	2.4 mm.
<u>Spreading rate:</u>	4Kg/m² or 0.45 liter/m² minimum (20lt = 9m²)
<u>Viscosity at 23°C :</u>	Paste.
<u>Flash point:</u>	Non-flammable.
<u>Respecting the environment:</u>	100% Lead Free. Dispose of excess product and containers in a responsible manner without harming the environment.

This product is manufactured under strict SABS ISO 9001 quality standards.

STORAGE:

Keep containers properly sealed. Store away from direct heat, sun and severe cold in a place with adequate ventilation.

PACKAGING:

5Lt, 20Lt

PROMINENT PAINTS RIPPLE TROWEL-ON

APPLICATION DETAILS:

<u>Mixing:</u>	Stir thoroughly with a flat paddle to an even consistency. Stir occasionally during use.
<u>Method:</u>	Trowel (Apply with a steel trowel and work to required effect with plastic trowel).
<u>Application:</u>	Ready for use with a rigid steel trowel. Load small quantities of Prominent Paints Ripple Trowel-On onto a mortar board for easy use. Spread the material evenly over the prepared and primed surface to be coated with a film thickness of approximately 2.4mm. Allow the Prominent Paints Trowel-On application to set for 10 minutes before polishing up with a plastic trowel; vertically for walls (up and down motion), or in circular motions for ceilings depending on the type of pattern that is required. Always keep tools clean for best application results.
<u>Thinning:</u>	Not recommended.
<u>Cleaning:</u>	Water.
<u>Conditions:</u>	Temperature between 5°C and 40°C. Relative humidity of less than 85%, preferably between 10:00 and 16:00.
<u>Drying time:</u>	Surface Dry: 4-6 Hours Hard Dry: 12-24 Hours.
<u>Recoating time:</u>	One coat system but if needed to recoat due to touch-ups recoat with Ripple Trowel-On from corner to corner after 24 Hours.
<u>Requirements:</u>	One coat system.

SURFACE PREPARATION:

Surfaces must be sound, clean and dry (moisture content below 15%) before painting.

New work:

1. Cement Plaster Apply 1 coat Prominent Paints Dampcure.
2. Concrete wall surfaces Concrete surfaces must be free from release agents. Remove releasing agent with ProGold General Purpose Cleaner and allow drying before priming with Prominent Paints Dampcure.
3. Bricks (unglazed) Apply directly.

Redecorating:

1. Emulsion paint Sand surface to matt finish, dust off and apply directly.
2. Gloss paint Sand surface to matt finish, dust off and apply Prominent Paints Universal Undercoat. Allow to dry and then apply.
3. Chalky or Lime washed surfaces Remove chalkiness with high pressure water at 180 KPA water pressure and rotating nozzle or with ProGold General Purpose Cleaner diluted 1:10 with water. While still wet abrade with abrasive pad, flush with water and allow to dry. Apply one coat Prominent Paints Dampcure thinned down with 20% ProGold Mineral Turpentine
4. Paint in poor condition Remove and treat as new work.

PROMINENT PAINTS RIPPLE TROWEL-ON

LIMITATIONS:

1. Specialist applicators required.
2. Touch-ups not possible. The section needs to be re-coated from corner to corner after 24 hours of the first coating application.
3. For a highly washable and scrubbable finish, overcoat with a flexible paint e.g. Prominent Paints Satin or Sheen.
4. Cannot handle structural movement.
5. The application to unsound, friable or powdery surfaces (new or old), is not recommended.
6. Do not apply to floors.

SAFETY PRECAUTIONS:

1. Keep out of reach of children.
2. Ensure to maintain good ventilation during application and drying process.
3. In case of skin contact, wash with soap and water or a recognised skin cleaner. Avoid contact with eyes. In case of contact with eyes rinse eyes immediately with running water and seek medical advice if.
4. If product is ingested drink plenty of water or milk. Do not induce vomiting at any time. Seek medical advice.
Refer to the Material Safety Data Sheet (MSDS) for detailed information about the product and transportation and classification criteria. MSDS is available on www.prominentpaints.co.za or from Prominent Paints Customer Service Department.
5. To avoid any risk of spillage, always transport in a secure upright position.

DISCLAIMER:

The information contained herein is given in good faith and is meant merely as a guide for the specifier or user. It is gained from results obtained from our experience and tests carried out under controlled conditions. No warranty/guarantee is implied since the conditions of use, application method, substrate and cleanliness of the substrate are beyond Prominent Paints control. For a surface specific specification contact Prominent Paints Customer Service Department for assistance. This issue supersedes all previous publications.

Important Note; Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used for reference. Prominent Paints Technical Data Sheets are available on www.prominentpaints.co.za or from Prominent Paints Customer Service Department.

Prominent Paints (Pty) Ltd.

11 Dan Jacobs Street.
Alrode Alberton 1449
P.O. Box 136166
Alberton North 1456

Reg. No. 1997/006763/07

Customer Service Department:
Tel: +27 86 177 6646
Fax: +27 11 389 4711
www.prominentpaints.co.za