

TECHNICAL DATA SHEET

PROMINENT BRICK DRESSING INTERIOR

Date: January 2026



THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

PRODUCT DESCRIPTION

Clear oil-based varnish for interior use.

INTENDED USES:

Protective coating for all brick work where a clear finish with good abrasion is required.

FEATURES:

1. Moisture repellent.
2. Resistant to peeling and cracking.
3. Provide good protection to brick surfaces.

PRODUCT INFORMATION:

<u>Appearance:</u>	Gloss
<u>Colours:</u>	Clear
<u>Solids:</u>	45% by mass; 53% by volume.
<u>Density:</u>	± 0,90Kg/litre.
<u>Recommended Dry Film Thickness:</u>	15 - 20µm.
<u>Spreading rate:</u>	10 - 15m ² /litre dependent on brick texture and porosity.
<u>Viscosity at 23°C:</u>	± 60Kµ.
<u>Flash point:</u>	23°C.
<u>Respecting the environment:</u>	Lead Free. Dispose of excess product and containers in a responsible manner without harming the environment.

This product is manufactured under strict SABS ISO 9001:2015 quality standards.

STORAGE:

Keep containers properly sealed.
Store away from direct heat, sun and severe cold in
a place with adequate ventilation.

PACKAGING:

1Lt, 5Lt, 20Lt

TECHNICAL DATA SHEET

PROMINENT BRICK DRESSING INTERIOR

APPLICATION DETAILS:

<u>Mixing:</u>	Stir well before use with a flat paddle to an even consistency. Stir occasionally during use.		
<u>Method:</u>	Brush.		
<u>Thinning:</u>	Mineral Turpentine.		
<u>Cleaning:</u>	Mineral Turpentine.		
<u>Conditions:</u>	Temperature between 5°C and 40°C. Relative humidity of less than 85%, preferably between 10:00 and 16:00.	<u>Conditions:</u>	Temperature between 5°C and 40°C. Relative humidity of less than 85%, preferably between 10:00 and 16:00.
<u>Drying time:</u>	Touch dry = 6 hours; Hard dry = 24 hours at 23°C.		

SURFACE PREPARATION

Surfaces must be sound, clean and dry (moisture content below 15%) before painting.

New work:

1. Thin first coat 10% with Mineral Turpentine. Apply the 2nd and 3rd coat undiluted.

Redecorating:

1. Surfaces in poor condition strip down and treat as new work.
2. Previously coated Brick Dressing Surface in good condition. Wash with General Purpose Cleaner diluted (1:5) with water and a nylon brush. Rinse with water and allow to dry. Apply directly.

TECHNICAL DATA SHEET

PROMINENT BRICK DRESSING INTERIOR

LIMITATIONS:

1. Use only in well-ventilated areas.
2. Surfaces must be dry with a moisture content of 15% or below.
3. Not UV stable – not to be used for exterior purposes.
4. Tinting not recommended.

SAFETY PRECAUTIONS:

1. Keep out of reach of children.
2. Ensure to maintain good ventilation during application and drying process.
3. Wear a suitable dust mask if sanding.
4. In case of accidental skin contact, wash with soap and water or a recognised skin cleaner. Avoid contact with eyes. In case of contact with eyes rinse immediately with running water and seek medical advice.
5. If product is ingested, drink plenty of water. Do not induce vomiting at any time. Seek medical advice.
6. Do not smoke while painting.
7. To avoid any risk of spillage, always transport in a secure upright position.
8. Refer to the Material Safety Data Sheet (MSDS) for detailed information about the product and transportation and classification criteria. MSDS is available on www.prominentpaints.co.za or from the Prominent Customer Service.

DISCLAIMER:

The information contained herein is given in good faith and is meant merely as a guide for the specifier or user. It is gained from results obtained from our experience and tests conducted under controlled conditions. No warranty/guarantee is implied since the conditions of use, application method, substrate and cleanliness of the substrate are beyond Prominent control. For a surface specific specification contact the Prominent Customer Service Department for assistance. This issue supersedes all previous publications.

Important Note: Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used for reference. Prominent Technical Data Sheets are available on www.prominentpaints.co.za or from the Prominent Customer Service Department.

Prominent (Pty) Ltd.
11 Dan Jacobs Street.
Alrode Alberton 1449
P.O. Box 136166
Alberton North 1456

Customer Service Department:
Tel: +27 86 177 6646
Tel: +27 11 389 4746

Reg. No. 1997/006763/07